



TECHNICAL DATA SHEET

ENERSAVE LEAK SEALER

IDENTIFICATION OF PRODUCT AND COMPANY

Product Name:	ENERSAVE LEAK SEALER
Use/Description:	Domestic central heating water treatment. Not suitable for use in PRIMATIC single feed cylinders.
Company Name:	Scalemaster Limited T/A Enersave Distribution Emerald Way, Stone Business Park, Stone, Staffordshire, ST15 0SR Tel: 01785 815117 Email: sales@enersavedistribution.co.uk

PRODUCT DESCRIPTION

ENERSAVE LEAK SEALER Sealer has been specially formulated for sealing small leaks and weeping joints in all types of closed heating and chilled water systems, including those containing aluminium. The product is compatible with most commonly used water treatment inhibitors.

ENERSAVE LEAK SEALER cures on contact with the air to form a watertight seal at the leaking joint. This will normally take 24 hours dependent on the rate of leakage and the temperature.

PRODUCT ADVANTAGES

- Seals small leaks and weeping joints without the need to drain the system
- Compatible with most commonly used water treatment inhibitors
- Easy to dose

PRODUCT APPLICATION

ENERSAVE LEAK SEALER is dosed to the system at a rate of 0.5% of the system volume. One 0.5 litre container contains sufficient product to treat a typical 100 litre/10 radiator system.

Open systems should be dosed via the system header tank*.

(*Product not to be used in central heating systems with single feed Primatic-type cylinders).

Closed systems should be dosed by addition to any convenient point if empty, or, if full, injected into a convenient access point following removal of sufficient system volume.

ENERSAVE LEAK SEALER can be left in the system permanently.

If the product is to be left in the system label the system in a prominent place with the product name and date of application.

Where system losses due to leaks are severe, further dosage of ENERSAVE LEAK SEALER may be required to maintain a suitable level of product in the system for future protection.

For best results add ENERSAVE INHIBITOR for protection from corrosion and limescale formation.

PRODUCT AVAILABILITY

ENERSAVE LEAK SEALER is available in 0.5 litre (500 ml) non-returnable plastic containers and is at a level of concentration sufficient to treat a typical 100 litre system.